



OS25

INDOOR/OUTDOOR LOUDSPEAKER



High Performance Indoor/Outdoor Loudspeaker

- Exceeds military anti-corrosion specifications (MIL-STD-883D)
- Easy three-way mounting system

OS Indoor/Outdoor Loudspeaker**OS25**

Color	Stock Number
Black	FG00893
White	FG00892



2002 Audio Video
International's Hi-Fi
Grand Prix Awards

WOOFER TECHNOLOGY

- 6-1/2" Injection-molded TCC (talc, carbon, and ceramic-filled) polypropylene cone is extremely rigid to reduce breakup and lower distortion
- Butyl rubber cone surround damps resonance and provides exceptional durability
- High BL magnet structure with vented pole piece insures powerful bass response

TWEETER TECHNOLOGY

- 1" Tri-laminate Teteron dome with fluid-cooling and ultra-wide dispersion for clear and detailed high-frequencies

SPECIFICATIONS

- Impedance: 4 ohms
- Recommended amplifier power: 5W to 150W
- Frequency response: 55Hz-21kHz +/-3dB
- Sensitivity: 91dB for 2.83V pink noise
- Dimensions (includes bracket): 13" high x 9-7/8" wide x 9" deep

Warranty: Two-year limited

Technology**WEATHERPROOF ENGINEERING**

Enables OS Loudspeakers to handle extreme hot, cold and moist environments.

ADVANCED MATERIAL SCIENCE

Elevates appearance and longevity of the cabinet and grille and enhances the performance of the woofers, tweeters and crossovers

ARCHITECTURAL FRIENDLY DESIGN

Delivers stellar acoustical performance yet tucks discretely away into corners and under eaves

LOW DIFFRACTION GRILLE AND FRONT Baffle

Ensures that the sound waves emanating from the woofer and tweeter are not reflected by the surrounding parts of the speaker for precise imaging and acoustical accuracy

RIGID, ACOUSTICALLY INERT CABINET

Prevents transmission of unwanted vibrations for clean and dynamic bass response

Details**ALL-WEATHER VERSATILITY**

Reduces installation limitations to provide great sound from the beaches of Miami to the harsh winters of Minneapolis

HOME THEATER APPLICABILITY

Enables OS Loudspeakers to be used as left, center, right, or surround speakers. OS10, OS20 and OS25 models are voice-matched to: HD8.3, HD8, HD6, HD5 in-wall and CM8HD, CM6HD, CM5HD ceiling mount loudspeakers

THREE-WAY MOUNTING SYSTEM

Provides a variety of secure, quick and easy mounting solutions

STABLE SHELF PLACEMENT

Allows OS Loudspeakers to be used as traditional bookshelf speakers

TAPERED SHAPE

Facilitates mounting in corners and under eaves

INVERTED GOLD PLATED 5-WAY BINDING POSTS

Repel moisture and ensure positive connections in virtually any conditions over long periods of time